




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F04B 49/06, B60S 5/04, A61H 23/04, A47C 27/08, G06K 19/07, A61G 7/057	A1	(11) International Publication Number: WO 00/06904 (43) International Publication Date: 10 February 2000 (10.02.00)
(21) International Application Number: PCT/GB99/02403 (22) International Filing Date: 23 July 1999 (23.07.99) (30) Priority Data: 9816173.0 25 July 1998 (25.07.98) GB (71) Applicant (for all designated States except US): HUNTLEIGH TECHNOLOGY PLC [GB/GB]; Group IPR Department, 310-312 Dallow Road, Luton, Bedfordshire LU1 1TD (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): NEWTON, Michael, David [GB/GB]; 8 Tyn Y Waun Road, Machen, Gwent NP1 8LA (GB). (74) Agent: THAKER, Shalini; Group IPR Department, Huntleigh Technology PLC, 310-312 Dallow Road, Luton, Bedfordshire LU1 1TD (GB).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: IDENTIFICATION AND COMMUNICATION SYSTEM FOR INFLATABLE DEVICES**(57) Abstract**

A pneumatic system consists of an inflatable/deflatable article, for example, a compression garment (21) connected to a pump (20) by connectors (12 and 11), respectively. The connector (12) attached to the garment (21) carries an RFID transponder (30) and a corresponding radio circuit (31) is located within the pump (20). In use, the transponder (30) transmits and receives information to and from the pump radio circuit (31). The information exchanged is used by the pump control system to activate the pump and to operate the pump to provide the particular operating parameters for that garment, for example, pressure, inflation/deflation cycle duration of treatment, etc.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

IDENTIFICATION AND COMMUNICATION SYSTEM FOR INFLATABLE DEVICES

This invention relates to pneumatic systems and in particular to pneumatic systems having an inflatable/deflatable article connected to a fluid source, for example a pump.

It is known for such systems to have a coupling assembly connecting the article to the fluid source, the coupling assembly comprising a male insert and a cooperating female receptacle for receiving the male insert so as to form a coupled state. The male insert or female receptacle includes a mechanical latch cooperating with a cavity on a corresponding surface of the other for mechanically latching and unlatching the coupling assembly, the male insert member and the female receptacle both defining a pathway for the flow of fluid through it when in the coupled state. A seal member extends between the male insert member surface and the surface of the female receptacle to provide a fluid tight seal when in the coupled state.

WO96/14785 describes a pneumatic system comprising an inflatable mattress connected to a pump by a connector mounted on the end of a fluid line from the inflatable mattress, the connector being mechanically inoperable upon disconnection with the pump. In this way, the connector ensures that the inflatable mattress is used only once, for reasons of clinical safety.

However, such pneumatic systems of the prior art including connectors that prevent re-use are not able to distinguish between different articles to be inflated or different pumps.

Modern technology has now made it possible to design a pump to be programmable so that a number of different inflatable articles with differing inflating and/or deflating arrangements fulfilling totally different functions may be attached to a physically identical pump. Thus, there is a need for an intelligent means associated with the pump and/or the article able to identify or distinguish between the pump and the article connected, and further to control the operation of the pump appropriate to the article connected.

Accordingly, the invention provides a pneumatic control system including a pump and at least one inflatable/deflatable article, control means for operation of the pump, connection means for connecting the article and pump for fluid flow therethrough, communication means provided on each of the pump and article, wherein upon connection between the pump and article at least one of said communication means capable of identifying the article and instructing the control means to activate the pump accordingly.

Preferably, the communication means are capable of exchanging information or energy so as to identify the article as that compatible to the pump and more preferably instruct the pump control means to operate a predetermined inflation and/or deflation of the article.

The information exchange between the article and the pump may comprise information contained in the article communication means being read by the pump communication means and used by the pump control means to operate the pump, or information contained in the article communication means being read by the pump communication means, and information modified/generated within the pump

communication means being stored within the article communication means during use. The information exchange may be by means of an energy source which may include but not be limited to electrical, pneumatic, acoustic, magnetic, electromagnetic or optical signals.

The modified information or energy transmitted to the pump is used to identify the article and thereafter used to control the pump operation either without user interface or to signal the user to operate the pump as indicated. Thus, operation of the pump may be altered automatically to match the requirements of the article to be inflated/deflated and its application.

Preferably, the information may include specific information, i.e. codes, to identify the article and/or its mode of operation (including pressure and flow versus time profile, and alarm settings) and/or security markings, to prevent unauthorised use.

In a preferred embodiment, the communication means on the article is located within the connection means connecting the article to the pump. Preferably, during use the respective communication means do not contact each other.

Examples of information contained within the article communication means may include some or all of the following data:-

- (i) Article serial number - for traceability in the event of customer complaint, product modification, recall or product ownership.
- (ii) Article manufacturing date - the pump communication means can automatically infer that an article with a limited storage time from manufacture to use is out of time and therefore will not operate the

pump, indicating so on the operator panel. This would be relevant to the case of single use sterile articles where the sterile packaging has a limited lifetime.

(iii) Article type information - the pump communication means reads the code and identifies the code as that to be used by the pump and sets up the correct pressure and flow versus time profiles on the air delivery paths automatically. Also the communication means on the pump can indicate to the user on the pump operator panel which application or applications the pump/article combination is intended for.

(iv) Single use/re-use information - indicates to the pump communication means to display on the operator panel whether the connected article is designed for re-use or for single use only.

(v) Duration of use information - this could either be in the form of the article in-use running hours or number of pressure time cycles per use or the actual times recorded when used. If this information is fed by the pump communication means back to the article communication means then it can be read by any pump communication means on subsequent usage. In this way users can be signalled when articles have reached the end of their operating life and for either clinical efficacy or safety reasons should no longer be used and whether user compliance of prescribed therapy has been administered. Also, the pump could be automatically shut-off or instructed to give appropriate warnings at the end of operating life/use.

(vi) Single Use Information - if the article communication means indicates application for single use only then the pump communication means can input in the

article communication means, an indication that the article has already been used. On subsequent attempts to use the article the pump communication means will recognise single use has occurred and not operate. In this case the clinical efficacy and safety of a single use article can be preserved automatically.

(vii) Limited or Multiple Re-use - if this is indicated within the article communication means then the pump communication means will automatically clock up the number of use cycles, put the information into the article communication means, and when the designed number of use cycles has been reached, the pump can automatically indicate this to the user so preserving clinical safety and efficacy.

(viii) Re-usable clinical articles after being re-processed (consequent to use to eliminate cross-contamination between users) - here the pump communication means looks for an indication from the article communication means that the article has been validly reprocessed between use cycles. This validity information is placed in the article communication means at the reprocessing facility using an approved piece of equipment. In this way only approved reprocessing which maintains clinical efficacy and safety will be accepted by the pump for use.

Another aspect of the invention provides for the use of the information exchange outlined above, in the field of intermittent compression therapy and pressure area care.

Therefore, a preferred embodiment of the invention provides a pneumatic control system including a pump and an inflatable/deflatable support for a patient to lie on,

control means to operate the pump, connection means for connecting the support and pump for fluid flow therethrough, wherein the pump and support have respective communication means, at least one said means
5 capable of identifying the article and to instruct the pump control means to activate the pump accordingly.

Preferably, the said communication means are capable of exchanging information or energy to identify the support and to instruct the pump control means to operate
10 the pump to provide a predetermined inflation/deflation of the support for a patient lying thereon. More preferably, the support communication means may be located within the connection means connecting the support to the pump.

15 A further preferred embodiment of the invention provides a pneumatic control system including a pump and at least one inflatable/deflatable garment to be wrapped around a user's limb, control means to operate the pump, connection means for connecting the garment and pump for
20 fluid flow therethrough, wherein the pump and garment(s) have respective communication means, at least one said means capable of identifying the garment(s) and instructing the pump control means to activate the pump accordingly.

25 Preferably, the said communication means are capable of exchanging information or energy to identify the garment(s) and to instruct the pump control means to activate the pump accordingly and more preferably to further operate the pump to provide a predetermined
30 inflation/deflation cycle of the garment(s) suited to the garments' application. Preferably, the garment

communication means may be located within the connection means connecting the garment to the pump.

The use of communication means to provide pressure area care and compression therapy will result in fewer individual pump models being required for the different care applications, all requiring differing pneumatic performance criteria and operator interfaces. This will lead both to manufacturing economies of scale and substantial acquisition, storage and inventory cost reductions, which is particularly beneficial within the cost sensitive and resource limited healthcare establishments where such care applications are generally used.

The communication means can be separately applied to pumps and to the garments and supports so long as the air delivery path configurations are functionally compatible. Thus pumps could operate such articles yet to be developed so long as the articles have their operating characteristics configured in a compatible communication means attached thereto.

In a healthcare environment this use of communication means prevents the inadvertent and unsafe operation of pump types with inflatable garments or supports e.g. pads or mattresses, which are not functionally safe or clinically compatible. A pump equipped with the communication means will readily deliver safe, effective therapy with a wide range of such inflatable articles.

The communication means of the present invention for information exchange between an article and a pump to control operation of the pump may comprise conventional read and write information systems; examples of which,

include bar code, magnetic stripe coding, insertion/rotation of co-operating connectors when connecting an article to the pump; geometry or intensity of magnetisation or transmissive or reflective optical path read by sensors; unique combinations of mechanical shapes read by mechanical switches or electronic memory chip with memory retention without power, for example, flash memory or EEPROM or UV EPROM.

Preferred embodiments of the present invention are described below, by way of example only, with reference to the accompanying drawings in which:

Figure 1 shows a schematic diagram of a communication means according to the present invention;

Figure 2 shows an alternative method of mounting one element of the communication means to that in Figure 1;

Figure 3 shows a typical radio communication means comprising a passive transponder and powering radio circuit; and

Figure 4 shows an alternative embodiment of a communication means.

Referring to Figure 1, the preferred embodiment consists of a pneumatic system consisting of a compression garment 21 connected to a pump 20 by a connector 10. The connector 10 has a connector part 11 connected to the pump 20 and a cooperating connector part 12 connected to the fluid line of the garment 21. The connector 12 carries a radio frequency identification device 30, i.e. a transponder. The transponder 30 is mounted on the connector part 12 connecting the compression garment 21 to the pump 20 and a corresponding radio circuit is located within the pump 20. The transponder 30 may be in the shape of an annular ring

fitted to the connector part 12 surrounding its fluid line outlet or any suitable shape to fit on or adjacent the connector 12. The transponder 30 typically comprises a coil acting as an antennae to transmit and receive signals, a capacitor to temporarily store energy to power the transponder, an integrated circuit to provide control and modulation functions and a read/write electronic memory (EEPROM). The transponder 30 is used to transmit and receive information to and from the pump radio circuit 31. As shown in Figure 3, radio circuit 31 in the pump comprises coils located close to the pump outlet to provide for transponder power and two-way communication between the transponder 30 and the circuit 31. The transponder 30 is passive and does not need any power to store information. It is energised by coming into proximity with the coils of the radio circuit 31 in the pump 20 and can then communicate with the pump circuit 31. As the transponder 30 does not need power to store information there is no need for connection cables or batteries and it may be completely sealed after assembly, within connector part 12 attached to the compression article 21.

The communication between the transponder 30 and pump 20 is controlled by hardware and software within the pump.

The operation of the pump 20 is programmable, specifically the operation in terms of applied pressure and flow versus time profiles and alarm monitoring. This is achieved by having the key parameters which control this operation stored in the transponder 30 to be read by the radio circuit 31 in the pump 20 and used to operate the pump accordingly. Thus by changing the garment 21

the operation of the pump 20 may be changed and hence the pump 20 may be programmable by the garment 21.

The general approach is for the pump software to signal to the transponder via the radio link a request to transmit certain operational parameters. These are received by the pump radio link and used as a basis to operate the pump. For example, if the pressure is specified for the article then the pump will provide that particular pressure.

10 It is the information stored in the transponder within the connector on the article which indicates to the pump to operate accordingly.

Specific examples of parameters include:

Operating parameters - operating pressure level, pressure versus time inflation rate, pressure versus time deflation rate, duration of inflation, duration of period between inflation's.

Alarm parameters, the pressure at which an inflation characteristic is detected, time at which this is tested, number of fault conditions prior to alarm occurring. This would be duplicated for each alarm condition.

In use, the connector parts 11,12 are joined together. The transponder 30 within the garment connector part 12 when coming into the vicinity of the pump's radio circuit 31 is powered and responds by transmitting a signal to the pump radio circuit 31. The radio circuit 31 may request further information from the memory of the transponder 30 or it may modify some of the transponder memory 30. The pump 20 processes the information it has read from the transponder 30 and accordingly provides the specific inflation requirements for that garment 21.

The pump 20 is reconfigured after any break in its operation, for reasons of it being switched off, powered off or another garment being connected.

The radio circuit 31 reads the information within
5 the transponder 30 memory on the connector part 12 of the garment 21 and identifies the garment 21 and if the information is compatible with that held within the pump 20 either electronically or within the software, then the pump operates the garment 21 according to the information
10 transmitted by the transponder 30. In the case of single-use garments, the transponder memory 30 may contain additional control information which instructs the pump not to re-inflate or not to inflate after a certain time or any other parameter based decision process.
15 Additionally, the radio circuit 31 may modify the transponder 30 memory to prevent further re-use of the garment 21 upon re-connection with the or another pump.

The pump 20 may be configured so that it is solely dependent on the transponder 30 memory to provide
20 information regarding the inflation requirements of the garment 21 attached. This allows for new garments to be connected and operated by the pumps without the pumps' having to be upgraded.

The pump radio circuit 31 and transponder 30 could
25 exchange information about the following:

The transponder 30 in the garment 21 could be used to store information about the pump's own operational history - e.g. time since last service, alarm history, degree of utilisation etc. This information could then be
30 accessed by the manufacturer or its agents without physically having to gain access to the pump. This is an advantage where the pumps are spread widely

geographically or where access is restricted due to commercial reasons.

The opposite arrangement is also possible where the pump radio circuit 31 captures all the usage information stored within the garment transponder 30 (which could be a history involving many pumps). During servicing of the pump 20 the information is accessed as part of the service procedure.

This sort of information would allow better understanding of the actual pump/garment usage in healthcare establishments which may provide useful information for commercial, product reliability and quality and clinical efficacy purposes.

The facility to remotely upgrade the operation/disable use/enable use of the pump is possible.

The pump could include a transponder itself to self check that its own radio circuit 31 is working and further could be adapted to accommodate an external transponder 50. The transponder 50 may be in the form of a programming key which when connected to the pump 20, in the vicinity of the radio circuit 31 would specifically configure the operation of the pump 20 and garments 21 together as a system for a specific patient in a healthcare environment. This key could be configured by a physician for a particular patient's requirements. The key would override any existing settings stored in the pump and/or garments and ensure that the required pump operation occurred. Thus, improved patient compliance and increased product safety and efficacy would result. Other transponders or similar could be used to log operational data for maintenance purposes.

The pneumatic system above describes a pump 20 having a radio circuit 31 communicating with a radio frequency identification device (RFID) 30 on a connector 12 to a garment 21. The radio circuit 31 within the pump 20 also contains a phase detection circuit which can be used to detect any change of phase due to external influences and this principle may be employed as an alternative communication means for the pneumatic system.

A number of materials can be used to change the phase of the coil 31, examples are shown in table 1.

Material	Phase Change in Degrees
Magnetically loaded plastic	+45
Torrid Core	+11
Amorphous metal strip	+50
Steel Core	-17
Cable screen ferrite 10mm	+62
Cable screen ferrite 5mm	+28
Brass Core	-22

In the case of brass the introduction into the coil field 31 lowers the phase detected by the phase detector, and conversely the use of ferrite increases the phase detected, resulting in different values for differing materials. The phase angle change can be controlled by the amount of material within the coil field and by this method several identities can be detected.

Figure 4 shows an alternative system using the pump 20 as in Figure 1 and a connector 12 to a garment 21 (not shown), the connector 12 having communication means including an annular ring of ferrite 40 around the fluid line outlet.

In use, as shown in Figure 4a the connector parts 11, 12 are joined together. The ferrite 40 when coming into the vicinity of the pump's radio circuit 31 increases the phase detected by the phase detection
5 circuit within the pump 20 and accordingly identifies the garment 21 (not shown) and if the phase change information is held to be compatible with the pump 20 either electronically or within the software, then the pump 20 may be operated to provide the therapy required.

10 While the preferred embodiments describe intermittent garments incorporating connectors having various types of communication means, it is understood that mattresses as well as any other inflatable/deflatable articles may be similarly connected and
15 inflated/deflated using the same principles according to the invention. Moreover, the respective communication means within the article and the pump may be located elsewhere than the connectors as in the preferred embodiment, for example, within the inflatable article
20 and/or pump casing. The preferred embodiments have described connectors using a means of information exchange or identification incorporating a radio frequency identification device (RFID) or ferrite material respectively, however any other forms of
25 information exchange devices as discussed earlier or as would be apparent to those skilled in the art are within the scope of the invention.

Claims:

1. A pneumatic control system including a pump and at least one inflatable/deflatable article, control means
5 for operation of the pump, connection means for connecting the article and pump for fluid flow therethrough, communication means provided on each of the pump and article, wherein upon connection between the pump and article at least one of said communication means
10 capable of identifying the article and instructing the control means to activate the pump accordingly.

2. A pneumatic control system as claimed in claim 1, wherein the communication means are capable of exchanging
15 information or energy so as to identify the article as that compatible to the pump and to instruct the pump control means to operate a predetermined inflation and/or deflation of the article by the pump accordingly.

20 3. A pneumatic control system as claimed in claims 1 or 2, wherein the communication means on the article is located within the connection means.

4. A pneumatic control system as claimed in claims 1, 2
25 or 3, wherein during use the respective communication means do not contact each other.

5. A pneumatic control system including a pump and an inflatable/deflatable support for a patient to lie on,
30 control means to operate the pump, connection means for connecting the support and pump for fluid flow therethrough, wherein the pump and support have

respective communication means, at least one said communication means capable of identifying the article and to instruct the pump control means to activate the pump accordingly.

5

6. A pneumatic control system as claimed in claim 5, wherein the said communication means are capable of exchanging information or energy to identify the support and to instruct the pump control means to operate the pump to provide a predetermined inflation/deflation of the support for a patient lying thereon.

7. A pneumatic control system as claimed in claim 5 or 6, wherein the support communication means may be located within the connection means connecting the support to the pump.


8. A pneumatic control system including a pump and at least one inflatable/deflatable garment to be wrapped around a user's limb, control means to operate the pump, connection means for connecting the garment and pump for fluid flow therethrough, wherein the pump and garment(s) have respective communication means, at least one of said communication means capable of identifying the garment(s) and instructing the pump control means to activate the pump accordingly.

9. A pneumatic control system as claimed in claim 8, wherein the said communication means are capable of exchanging information or energy to identify the garment(s) and to instruct the pump control means to activate the pump accordingly and to instruct the pump to

control means to operate the pump to provide a predetermined inflation/deflation cycle of the garment(s) suited to the garments' application.

- 5 10. A pneumatic control system as claimed in claim 8 or 9, wherein the garment communication means may be located within the connection means connecting the garment to the pump.

Fig.1.







Fig.3.





Fig.4.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/02403

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 F04B49/06 B60S5/04 A61H23/04 A47C27/08 G06K19/07
A61G7/057

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F04B B60S A61H A47C G06K A61G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 214 678 A (M BRINDLEY) 6 September 1989 (1989-09-06)	1-4
A	page 3, line 19 -page 5, line 9 page 6, line 5 - line 8; figures ---	5,8
X	WO 94 04398 A (ACKERMANN GEORG) 3 March 1994 (1994-03-03)	1-4
A	page 3, line 18 - line 35 page 4, line 7 -page 5, line 10 page 10, line 30 -page 12, line 20; figures ---	5,8
P,X	GB 2 323 453 A (KING ANDRE ALAN DONALD) 23 September 1998 (1998-09-23)	1-4
A	page 2, line 15 - line 22 ---	5,8
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

13 January 2000

Date of mailing of the international search report

20.01.00

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Jones, T

INTERNATIONAL SEARCH REPORT

Inter. Application No

PCT/GB 99/02403

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 96 14785 A (LAKE MEDICAL PRODUCTS, INC.) 23 May 1996 (1996-05-23) cited in the application abstract; figures ----	5
A	US 5 681 339 A (MCEWEN ET AL.) 28 October 1997 (1997-10-28) abstract; figures 1,2 ----	8
A	FR 2 678 825 A (FLEURY) 15 January 1993 (1993-01-15) page 3, line 15 - line 33; figures -----	8

INTERNATIONAL SEARCH REPORT

Int. application No.

PCT/GB 99/02403

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-4

1.1 Claims: 1,2

A pneumatic control system as in claim 1 to instruct the pump to operate a predetermined inflation.

1.2 Claims: 1,3

A pneumatic control system as in claim 1, with the communication means within the connection means.

1.3 Claims: 1,4

A pneumatic control system as in claim 1, wherein the communication means do not contact each other.

2. Claims: 5-7

A pneumatic control system as in claim 1, wherein the article is a support for a patient to lie on.

3. Claims: 8-10

A pneumatic control system as in claim 1, wherein the article is an inflatable garment.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/02403

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2214678 A	06-09-1989	NONE	
W0 9404398 A	03-03-1994	DE 9210798 U AU 4697793 A	23-09-1993 15-03-1994
GB 2323453 A	23-09-1998	NONE	
W0 9614785 A	23-05-1996	US 5584084 A AU 4159696 A CA 2205375 A EP 0792116 A	17-12-1996 06-06-1996 23-05-1996 03-09-1997
US 5681339 A	28-10-1997	AU 3021497 A W0 9806373 A EP 0917453 A US 5935146 A	06-03-1998 19-02-1998 26-05-1999 10-08-1999
FR 2678825 A	15-01-1993	AU 2328292 A W0 9300875 A	11-02-1993 21-01-1993